



P.O. Box 554, Portland, OR; 97207  
 503-292-8682 (Phone) 800-722-8078 503-292-8697 (Fax)  
 info@pr-tech.com sales@pr-tech.com

**Obstruction Lights**



**D-2/3LVS Controller**  
**Triple FAA Type L-864/L-865**  
**Dual Red/White Strobe Beacon**

Specifications	
Lightning Protection	MOVs, Isolation Transformer & Surge Protector
Alarms	Form "C," Power Fail, Photocell, Red Beacon Fail, Strobe Fail & Sidelight Fail
Service-Related Features	Modular Construction, Training Classes, Service Contracts, Installation & 24/7 Technical Support
Other Equipment Needed	Cable or Conduit Lighting Kit
Warranty Period	2 Years Limited
Meets FAA	AC-150/5345-43E
Applications	Tower, Chimneys, Cooling Towers, Bridges, Buildings, Wind Turbines & Custom Structures
Enclosure	Stainless Steel
Dimensions (HxWxD)	36.75" x 33" x 9" (93.35 x 83.82x 22.86 cm)
Mounting Dimensions (HxW)	37.375" x 24" (94.93 x 60.96 cm)
Weight	210 lbs. (95.45 kg)
Cable (Diameter/Weight Per 100 ft.)	0.625" ± 10% / 24 lbs. (15.875 mm ± 10% / 10.9 kg)

**OPTIONS**

Integrated alarm monitoring system complete with real time on-screen diagnostic capability. Combine one of our fully integrated monitoring systems with our monitoring software to take full advantage of the features that it has to offer.

**Features**

- User Friendly Software
- Remote Diagnostic Control
- Remote Light Operation Control
- Trigger Voltage Reading
- Temperature Reading
- AC Power Reading
- Capacitors Voltage Reading
- Alarm Reporting to a Pager
- Photocell Monitoring
- Real-time Clock Photocell Backup
- Light Failure Monitoring
- Integrated NOTAM Form
- Monitor All Light Systems
- Interfaces with Card Access Systems
- Strobes are Fully Integrated

503-292-8682 (Phone) info@pr-tech.com 800-722-8078 sales@pr-tech.com 503-292-8697 (Fax)

Copyright © 2003 P&R Technologies www.pr-tech.com