



P.O. Box 554, Portland, OR; 97207
 503-292-8682 (Phone) 800-722-8078 503-292-8697 (Fax)
 info@pr-tech.com sales@pr-tech.com

Incandescent Obstruction Lights

OL1 NEON FAA Type L-810



FEATURES

- Available as complete fixture.
- Fits all commonly used sidelights bases.
- Only NEON sidelight on the market that is a simple screw in design.
- Screw in bulb design doesn't require replacement of fixture.
- Low power consumption, reduces power needs by 50% over today's obstruction lights.
- Meets FAA compliance guidelines.
- Extremely reliable with a 5 year warranty.

Specifications

Intensity	Low
Horizontal Coverage	360 °
Lamp Description	Helical Neon
Vertical Beam	10 ° Minimum
Effective Candelas (Night)	32.5 Minimum
Flashhead Height	7.5" (19.05 cm)
Flashhead Diameter	4.875" (12.38 cm)
Flashhead Lens Material	Annealed Glass
Flashhead Base Material	Cast A356 Aluminum
Power Requirements	120V / 240V AC 50/60 Hz - Other voltages available
Wattage	60 Watts
Weight	3.125 lbs. (1.42 kg)
Operating Temperature	-55 °C to +55 °C
Wind Load	CAAA 0.2 ft ²
Hub Sizes	0.75", 1" Or 1.25" NPT

503-292-8682 (Phone) info@pr-tech.com 800-722-8078 sales@pr-tech.com 503-292-8697 (Fax)

Copyright © 2003 P&R Technologies www.pr-tech.com