



P.O. Box 554, Portland, OR; 97207  
 503-292-8682(Phone) 800-722-8078 503-292-8697(Fax)  
 info@pr-tech.com sales@pr-tech.com

## Obstruction Lights

### OL1 LED FAA TYPE L-810 SINGLE OBSTRUCTION LED LIGHT Features



- Available as complete fixture.
- Fits all commonly used sidelights bases.
- Only LED sidelight on the market that is a simple screw in design.
- Screw in bulb design doesn't require replacement of fixture.
- Very low power consumption, reduces power needs by 87% over today's obstruction lights.
- Meets FAA compliance guidelines.
- Extremely reliable with a 5 year warranty.

### Specifications

Intensity	Low
Horizontal Coverage	360°
Lamp Description	LED Array
Vertical Beam	10° Minimum
Effective Candelas (Night)	32.5 Minimum
Flashhead Height	9" (22.86 cm)
Flashhead Diameter	4.875"(12.38 cm)
Flashhead Lens Material	Annealed Glass
Flashhead Base Material	Cast A356 Aluminum
Power Requirements	120V AC 60 Hz - Other voltages available
Wattage	15 Watts
Weight	3.632 lbs. (1.65 kg)
Operating Temperature	-55°C to +55°C
Wind Load	CAAA 0.2 ft <sup>2</sup>
Hub Sizes	0.75", 1" Or 1.25" NPT