




P.O. Box 554, Portland, OR; 97207
 503-292-8682 (Phone) 800-722-8078 503-292-8697 (Fax)
 info@pr-tech.com sales@pr-tech.com

SolarPower

Siemens Photovoltaic Modules


Siemens SP Series



- 36 Powermax 5" semi-round single-crystalline cells.
- Conduit-ready junction box includes bypass diodes.
- Dual voltage capability at 6 and 12VDC.
- Rugged Universal frames.
- UL Listed / FM approved / TÜV / CE.
- 25 year power warranty for the larger 75 watt modules, 10-year limited on 18 to 36 watt modules.

	Wattage Peak (watts)	Warranty (years)	Weight (LBS)
SP18	18.	10	6
SP75	75.	25	17

Siemens SM Series



- SM-110 & SM-55 has 36 PowerMax ® single-crystalline solar cells (SM10 has 34, SM20 has 30, SM6 has 33, SM46 has 30, SM50-H has 33)
- 12V output (SM110 available in 24V output)
- 20 watts and below: Sealed terminal cover including color-coded lead wires for fast, safe, and easy field connections.
- 46 watts and above: Conduit-ready ProCharger™ junction box. (The SM46, SM50 and SM55 models have separate positive and negative junction boxes.)
- Rugged universal frames.
- UL Listed (except SM110) / FM approved (SM6, 10, 20, 50 -J & 55-J) / IEC 61215 (SM50 & 55) / TÜV (except SM110) / CE / MIL Standard 810 (except SM6, 10 & 110)
- 25-year power warranty. (10-year on SM6, 10 & 20.)

	Wattage Peak (watts)	Warranty (years)	Weight (LBS)
SM110	110.	25	28
SM110-24	110.	25	28
SM46	46.	25	10
SM50-H	50.	25	12
SM55	55.	25	12

Siemens ST Series



- Proprietary multiple-layer CIS solar cells, tempered glass front.
- 12V output.
- Two-conductor, 5' UV stable cable installed in a potted junction box.
- Black-anodized universal frames.

- TÜV / CE certification.
- 10 Year limited warranty on power output.

	Wattage Peak (watts)	Warranty (years)	Weight (LBS)
ST5	5.	5	5
ST10	10.	5	7
ST20	20.	10	12
ST40	40.	10	20

503-292-8682 (Phone)

info@pr-tech.com

800-722-8078

sales@pr-tech.com

503-292-8697 (Fax)

Copyright © 2003 P&R Technologies www.pr-tech.com